



ADV-8104 is high quality 4-Channel professional video/audio encoder with powerful functionality. It has 4 independent encoding channels with choice of SDI with embedded audio or HDMI with embedded audio inputs.

It supports MPEG-2 and H.264 video encoding and MPEG-1 Audio layer 2, LC-AAC, HE-AAC and Dolby Digital AC3 audio encoding.

ADV-8104 has 2 ASI outputs and IP output port. Four encoding programs can be output as 4 SPTS or one MPTS.

### Key Features

- Choice of 4 SDI or 4 HDMI video inputs with embedded audio
- H.264/MPEG-4 AVC and Mpeg2 HD/SD video encoding
- MPEG1 Layer 2, LC-AAC, HE-AAC, Dolby Digital AC3 audio encoding
- ASI multiplexed output (MPTS)
- IP outputs (MPTS and 4 SPTS) over UDP, RTP
- CC (closed caption ), EIA 608 and EIA 708 for SDI interface
- Built-in multiplexer
- Low Latency function
- PSI/SI editing and inserting
- IP null packet filter
- VBR/CBR video encoding
- LCD / keyboard and Web-based NMS control
- Dual power supply

## Technical Specifications

### Encoding

#### Video

Encoding	MPEG2 & MPEG4 AVC/H.264
Input	HD-SDI*4 or HDMI*4
Resolution	1920*1080_60P, 1920*1080_50P, (-for MPEG4 AVC/H.264 only) 1920*1080_60i, 1920*1080_50i, 1280*720_60p, 1280*720_50P 720*480_60i, 720*576_50i
Bit Rate	0.5~19.5Mbps for H.264 encoding 1~19.5Mbps for MPEG-2 encoding
Rate Control Mode	CBR/VBR
Chroma Sample	4:2:0
Aspect Ratio	16:9, 4:3

#### Audio

Encoding	MPEG1 Layer II, MPEG2-AAC, MPEG4-AAC, Dolby Digital AC3
Sample rate	48KHz
Bit rate	64kbps, 96kbps, 128kbps, 192kbps, 256kbps, 320kbps

### System

Local interface	LCD + control buttons
Remote management	Web NMS
Low Latency Mode	Normal, mode 1, mode 2
Output	2*ASI out (BNC type); IP (1 MPTS & 4 SPTS) over UDP, RTP (RJ45, 100M)
NMS interface	RJ45, 100M

### General

Power	AC 100V~240V, 45W
Dimensions	482*400*44mm
Weight	4.5 kgs
Operation temperature	0~45°C

## Ordering Info

**ADV-8104-S - 4-channel H.264/MPEG-2 HD/SD encoder with 4 SDI inputs**

**ADV-8104-H - 4-channel H.264/MPEG-2 HD/SD encoder with 4 HDMI inputs**

**ADV-8104-SH - 4-channel H.264/MPEG-2 HD/SD encoder with 2 SDI and 2 HDMI inputs**